EQUIPMENT TOUCH EQT3 DISPLAYS

The Equipment Touch EQT3 displays are rugged, industrial grade interfaces providing technicians with easy access to the equipment status, parameter values, schedules, alarms, and trends.

Designed for panel or wall mounting, they can load existing Equipment Touch files or new Custom Touch files built in ViewBuilder. The displays offer a contemporary design and include an IP65 rating on the front of the display, a wide temperature range and vibration resistance.

The user interface features are simple to operate for end users, but powerful enough to provide technicians a complete interface for maintaining equipment.


Key Features

- Available in four sizes (4.3", 7", 10.1", and 15")
- Rugged, industrial grade front display suitable for mechanical rooms or board room mounting
- Rnet connection or Service Port (either Ethernet or USB) connection
- Fully customizable touchscreen for navigation and control with ViewBuilder
- Default system screens such as scheduling and trends
- Supports international languages
- Support for graphics and animations
- Screen captures can be saved to a USB flash drive
- Built-in PDF viewer

Benefits*

- Multi-level password protection for security
- Custom screens can show equipment graphic and operating status
- Ability to view/edit controller configuration for BAS integration (service port connection only)
- Ability to view and/or edit equipment configuration, schedules, trends, and alarms with pre-designed screens
- Trending with support for pinch zoom and swiping to move along time line
- Works great as a technician tool and as a user interface

*A custom equipment touch file is required



- 1. LED for Power
- 2. Power Terminal Block
- 3. USB OTG 4. RJ45/LAN
- 5. Reset Button
- 6. RS485 Rnet
- 7. USB Port

Equipment Touch 15.1" display Part# EOT3-15



• EMCtr

Equipment Touch 10.1" display Part# EQT3-10



Equipment Touch 7" display Part# EQT3-7



Equipment Touch 4.3" display Part# EQT3-4



Specifications

	EQT3-4	EQT3-7	EQT3-10	E	QT3-15	
Power: 50-60 Hz, Class 2 Display: TFT Resolution Brightness Contrast Ratio Viewing Angle Max Colors Touchscreen	24 Vdc, .375A 4.3" TFT (Widescreen) 480 x 272 pixels (128 ppi) 400 cd/m (typ.) 1000:1 (typ.) -75~50(H); -75~75(V) 16.7M (8-bit) Projected Capacitive Multi	24 Vdc, .375A 7" TFT (Widescreen) 1024 x 600 pixels (170 ppi) 320 cd/m (typ.) 1000:1 (typ.) -75~70(H); -75~75(V) 16.7M (8-bit) i-Touch (P-CAP) (same for all)	24 Vdc, .417A 10.1" TFT (Wides 1280 x 800 pixel 350 cd/m (typ.) 800:1 (typ.) -85~85(H); -85~8 16.7M (8-bit)	creen) 1 s (149 ppi) 1 4 5 5(V) -{	24 Vdc, .417A 5.6" TFT (Widescreen) 366 x 768 pixels (252 ppi) 400 nits 500:1 (typ.) 85~85(H); -85~80(V) 6.7M (8-bit)	
Operating Conditions Storage Temperature	-4°F to 122°F (-20°C to 50° 10% to 90% RH (non-conc Front IP65 water and dust Vibration tested to EN 600 -13°F to 158°F (-25°C to 70	lensing) proof (rear: IP20))68-2-64		B		
Communication Ports	Comm Input Port: EIA-485 port for connection to the Rnet network (115kbps) USB Port: for upgrades, file copying, screen captures and connection to service port on controllers Micro USB On The Go (OTG) Port: for factory programming (firmware upgrades) LAN Port: RJ-45 Ethernet connection to service port on controllers Wall Mounting Kits also available: Parts: EQT3-7-MOUNT, EQT3-10-					
System Processor System Memory	OS: Android 11.0 MT8365 Quad-core Corte: (4", 7". & 10" models) 3 GE (15" model) 4 GB LPDDR4	B LPDDR4 RAM	Δ · 121		MOUNT	
Storage	32 GB onboard eMMC Fla		B : 82 r	nm (3.23")	E : 74 mm (2.91") F : 42 mm (1.65")	
Certifications	CE (Class B), FCC (Class B), CAN/CSA C22.2 No. 62368-1-14, ANSI/UL (62368-1, 2nd Ed), Vibration tested to EN 60068- 2-6, IP65 rated (front) IP20 rated (rear)		I-14, 68-	C: 49 mm (1.93") F: 42 mm (1.65") EQT3-7 Dimensions A: 185 mm (7.28") D:175 mm (6.89")		

Sample Screenshots



☆ ◀	Inputs	& Οι	Itputs		6
====== Outµ	outs ====				A
BO # 1: Fan: 🧿	Lock:	0N	OFF	AUTO	
BO # 2: Comp 1: 🧿	Lock:	ON	OFF	AUTO	
BO # 3: Comp 2: 🧕	Lock:	ON	OFF	AUTO	
BO # 4: Rev: Cooling	Lock:	ON	OFF	AUTO	
BO # 5: EH 1: 🕥	Lock:	ON	OFF	AUTO	T

•EMCtrl

Unit Status Occupied Zone Temp: 78.3 °F Mode: Cooling Alarm: Normal Schedule Trends



: 185 mm (7.28") **D**:175 mm (6.89")

A . 105 mm (7.20)	\mathbf{D} . (0.05)
B : 128 mm (5.04")	E : 118 mm (4.65")
C : 46 mm (1.81")	F : 39 mm (1.52")

EOT3-10 Dimensions

`	
A : 267 mm (10.5")	D : 244 mm (9.61")
B : 182 mm (7.17")	E : 159 mm (6.26")
C : 47 mm (1.85")	F : 39 mm (1.52")

EQT3-15 Dimensions

A : 421 mm (16.57")	D : 388.4 mm (15.29")
B : 260.5 mm (10.26")	E : 195.5 mm (7.7")
C : 52.5 mm (2.07")	F : 46.5 mm (1.83")



All trademarks used herein are the property of their respective owners.

A Carrier Company ©2024 Carrier. All Rights Reserved.

1025 Cobb Place Boulevard, Kennesaw, GA 30144 770-429-3060 | oemctrl.com