QUIPMENT TOUCH

T3 DISPLAYS

The Equipment Touch EQT3 displays are rugged, industrial grade interfaces providing technicians with easy access to the equipment status, parameter values, schedules, alarms, and trends.

Designed for panel or wall mounting, they can load existing Equipment Touch files or new Custom Touch files built in ViewBuilder. The displays offer a contemporary design and include an IP65 rating on the front of the display, a wide temperature range and vibration resistance.

The user interface features are simple to operate for end users, but powerful enough to provide technicians a complete interface for maintaining equipment.


Key Features

- Available in four sizes (4.3", 7", 10.1", and 15")
- Rugged, industrial grade front display suitable for mechanical rooms or board room mounting
- Rnet connection or Service Port (either Ethernet or USB) connection
- Fully customizable touchscreen for navigation and control with ViewBuilder
- Default system screens such as scheduling and trends
- Supports international languages
- Support for graphics and animations
- Screen captures can be saved to a USB flash drive
- Built-in PDF viewer

Benefits*

- Multi-level password protection for security
- Custom screens can show equipment graphic and operating status
- Ability to view/edit controller configuration for BAS integration (service port connection only)
- Ability to view and/or edit equipment configuration, schedules, trends, and alarms with pre-designed screens
- Trending with support for pinch zoom and swiping to move along time line
- Works great as a technician tool and as a user interface

*A custom equipment touch file is required



- 1. LED for Power
- 2. Power Terminal Block
- 3. USB OTG
- 4. RJ45/LAN
- 5. Reset Button
- 6. RS485 Rnet
- 7. USB Port

Equipment Touch 15.1" display

Part# EQT3-15



Equipment Touch 10.1" display

Part# EQT3-10



Equipment Touch 7" display

Part# EQT3-7



Equipment Touch 4.3" display

Part# EOT3-4






Specifications

	EQT3-4	EQT3-7	EQT3-10
Power: 50-60 Hz, Class 2 Display: TFT Resolution Brightness Contrast Ratio Viewing Angle Max Colors Touchscreen	24 Vdc, .375A 4.3" TFT (Widescreen) 480 x 272 pixels (128 ppi) 400 cd/m² (typ.) 900:1 (typ.) -80-60(H); -80-80(V) 16.7M (8-bit) Projected Capacitive Multi	24 Vdc, .375A 7" TFT (Widescreen) 1024 x 600 pixels (170 ppi) 320 cd/m² (typ.) 1000:1 (typ.) -75~75(H); -75~70(V) 16.7M (8-bit) 1-Touch (P-CAP) (same for all)	350 cd/m ² (typ. 800:1 (typ.) -85~85(H); -85~ 16.7M (8-bit)
Operating Conditions Storage Temperature	-4°F to 122°F (-20°C to 50°C) 10% to 90% RH (non-condensing) Front IP65 water and dust proof (rear: IP20) Vibration tested to EN 60068-2-64 -13°F to 158°F (-25°C to 70°C)		
Communication Ports	(115kbps) USB Port: for upgrades, fi to service port on controll Micro USB On The Go (O' (firmware upgrades)	5 port for connection to the le copying, screen captures a ers TG) Port: for factory progran connection to service port or	and connection
System Processor System Memory Storage	OS: Android 11.0 MT8365 Quad-core Corte: (4", 7". & 10" models) 3 GE (15" model) 4 GB LPDDR4 32 GB onboard eMMC Fla	GB LPDDR4 RAM R4 RAM R4 RAM Glash storage B: 82 B: 82 C: 49 C: 49	
Certifications			

T3-10 **EQT3-15**

dc, .417A 24 Vdc, .417A TFT (Widescreen) 15.6" TFT (Widescreen) 0 x 800 pixels (149 ppi) 1366 x 768 pixels (100 ppi) cd/m² (typ.) 400 cd/m² (typ.) 1 (typ.) 500:1 (typ.) 85(H); -85~85(V) -85~85(H); -85~80(V) M (8-bit) 16.7M (8-bit)



Wall Mounting Kits also available: Parts: EQT3-7-MOUNT, EQT3-10-**MOUNT**

EQT3-4 Dimensions

A: 121 mm (4.76") **D**:110 mm (4.33") **B**: 82 mm (3.23") **E**: 74 mm (2.91") **C**: 49 mm (1.93") **F**: 42 mm (1.65")

A: 185 mm (7.28") **D**:175 mm (6.89") **B**: 128 mm (5.04") **E**: 118 mm (4.65") **F**: 39 mm (1.52") **C**: 46 mm (1.81")

A: 421 mm (16.57") **D**: 388.4 mm (15.29") **B**: 260.5 mm (10.26") **E**: 195.5 mm (7.7")



EQT3-7 Dimensions


EQT3-10 Dimensions

D: 244 mm (9.61") **A**: 267 mm (10.5") **B**: 182 mm (7.17") **E**: 159 mm (6.26") **C**: 47 mm (1.85") F: 39 mm (1.52")

EQT3-15 Dimensions

C: 52.5 mm (2.07") **F**: 46.5 mm (1.83")





Sample Screenshots

Zone Temp:

Home

Schedule

75 🛞

70 🌽



All trademarks used herein are the property of their respective owners.

Unit Status

Zone Temp: 78.3 °F

Trends

Mode: Cooling

Alarm: Normal

Schedule